









LATIM is a supplier of long standing in steel coils and sheets, with a reputation of reliable product among trade and end-customers. It has launched a state-of-the-art range of galvalume / galvanized pre-painted steel coils manufactured at its advanced Colour Coating Plant in Umbergaon, Gujarat in Western India.

LATIM offers the following advantages:

- ☑ Speedier Delivery
- ☑ Exceptional Corrosion Resistance
- ✓ Optimum Product Life

To any end customer, the things that matter the most are the aesthetic impact of the product, the colour availability, and the long service life of the product. With LATIM, they can experience the threefold advantages of pre-painted steel viz. aesthetic appeal, variety of colours and durability with corrosion resistance.

Customers do not have to wait for delivery anymore. LATIM offers a wide range of coils in various thicknesses and specifications. It has established itself as a quality leader with the exceptional finish and dazzle of its colour coated steel coils. Uniform in colour, gloss and texture with excellent paint adhesion, they are produced on high technology coil coating line under stringent quality controls.

To ensure superior product performance for our customers, LATIM Colour Coated Coils undergo several tests – hardness, heat resistance, flexibility and bending, chemical resistance, impact, MEK solution, salt solution etc.

Product versatility:

- Structurally strong yet light in weight
- Appealing colour range where surface doesn't flake or peel
- High resistance to corrosion
- Ease of installation and zero maintenance

Besides their common use as roofing, cladding, false ceiling, LATIM colour coated steel coils are extensively used in several sectors - automotive fabrication, industrial infrastructure, warehousing, retail spaces, white goods, electrical, construction, and furniture.


















PERFORMANCE TESTING

Scratch Hardness (T / B)	1.5 - 2 / 1 - 1.5 Kg		
Impact Test (in Joules) (thickness based soft material)	As per standard		
Salt Spray Test (specific to coating type)	750 - 1000 hrs.		
Adhesion Test (cross-hatch)	100%		
Erichsen Cupping Test	As per standard		
Humidity Test	750 - 1000 hrs.		
T-Bend Test (T=substrate thickness)	2T for soft, 4T for hard (no tape loss)		
Water Boiling Test	As per standard		
Solvent Rub Test (MEK-double rub)	100 DR for non-metallic, 80DR metallic		
Chemical Resistance	As per standard		
Max. Operating Temp	Up to 140* C		

PRODUCT SPECIFICATIONS

COIL FORM	PPGL / PPGI
Thickness (mm)	0.16 - 1.00
Coil ID (mm)	508
Width (mm)	750 - 1450
Coil Weight (t)	2 - 6 mt
Substrate	Al-Zinc Alloy Steel / Galvanized
Al-Zinc Alloy Steel (gsm)	AZ 40 - 100
Zinc (gsm)	Z 40 / Z 120
Characteristics Primer (micron)	3μ to 7μ (max) Subject to Substrate & Coating Type
Top Coating (μ)	10 - 25
Back Coating (μ)	3 - 10
Hardness (HRB)	55 - 65 HRB Soft CQ, 85 HRB and above Hard
Guard Film - Optional (microns)	30 - 40µ


PAINT SPECIFICATIONS

Paint System* Primers	Epoxy, PU Polyester / Universal Top Coat Regular Modified Polyester (RMP / SMP / PVDF / SDP)			
Backer Coat	Epoxy, Polyester & PU			
Colour	As per RAL code / Customer's Requirement			
Gloss	Matt 35% (+/- 8%)			
Gloss	Semi Gloss 60% (+/- 10%), High Gloss > 70%			

PAINT PROPERTIES COMPARISION

Properties	SUPER / HIGH Durable Polyester	RMP	SMP	PVDF	PVC
Flexibility	Good	Fair	Poor	Good	Excellent
UV Resistance	Good	Fair	Fair	Excellent	Good
Gloss Retention	Excellent	Good	Good	Poor	Fair
Chalking Resistance	Good	Fair	Fair	Excellent	Fair
Costs	Marginal	Lowest	High	Very High	High
Durability Years	10	8	10	15	
SST Hrs.	1000	750	750	1000	1000

ADVANCED PAINT TECHNOLOGY





LATIM's high quality coloured / pre-painted galvanized / galvalume steel coils can be used for various Applications - Roofings, Claddings, Crimping, Warehouse, Cold Storage, Furnitures, False Ceilings, Shutter Doors, Vehicle Bodies, Decorative Container & Trunks, etc.

Ideal for Interior and Exterior Applications.

- Coloured / pre-painted sheet in various profiles available (against specific orders)
- Available in various thickness, sizes and colours

STANDARD COLOUR RANGE



Colours may vary from the shades shown above.



LA TIM METAL & INDUSTRIES LTD.

Corporate Office:

401, Navkar Plaza, 4th floor, Bajaj Road, Vile Parle (West), Mumbai - 400056.

Tel.: (022) 26202299, 26203399, 26203434, 26201166,

• E-mail : sales@latimsourcing.com • Web : www.latimprofile.com

Works: